



X4 ROVR SPECIFICATIONS

AUTONOMOUS FLOOR SCRUBBER

Operating system	BrainOS®
Learning type	Teach & Repeat and Area Fill
Scrubbing path	20 in / 500 mm dual disk
Estimated coverage per solution tank	20,000 ft ² / 1,860m ²
Squeegee	21.7 in / 551 mm
Solution tank	10 gal / 38 L
Recovery tank	10 gal / 38 L
Demisting chamber	3 gal / 11.4 L
Brush/pad rpm	220 rpm
Brush/pad downforce	up to 42 lbs / 19 kg
Battery	Lithium-Ion, 90 Ah (qty: 1)
Cleaning tool attachment	Insta-Click®
Autonomous scrubbing battery time	up to 2.5 hrs
Autonomous solution delivery system	Velocity-controlled
Conventional scrubbing - pumped solution flow rates	Low: 0.08-0.18 GPM variable Med: 0.08-0.24 GPM variable High: 0.08-0.35 GPM variable
Charger type	on-board
Charger specs	50/60Hz, 100-240 VAC
System voltage	25.6 volts
Vacuum motor	0.6 hp / 0.45 kW
Standard sound level	as low as 66dBA
Aisle navigation	as low as 28 in / 71 cm
Aisle entrance (90 degree)	as low as 3 ft / .91 m
Aisle u-turn	as low as 4.5 ft / 1.37 m
Machine height	44 in / 112 cm
Machine length	38 in / 96 cm
Machine width	22 in / 56 cm
Autonomous distance to wall	as low as 3 in / 7.6 cm
Weight (tanks empty, with battery)	403 lbs / 183 kg

For a complete selection of genuine Tennant parts, brushes and pads, please consult the X4 ROVR Parts and Consumables Reference Guide